

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 April 2003 (24.04.2003)

PCT

(10) International Publication Number
WO 03/034770 A1

(51) International Patent Classification⁷: **H04Q 7/38**

(21) International Application Number: **PCT/NO02/00377**

(22) International Filing Date: 18 October 2002 (18.10.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20015133 19 October 2001 (19.10.2001) NO

(71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET LM ERICSSON [SE/SE];**
S-126 25 Stockholm (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **EVENSEN, Thommy**
[NO/NO]; Ravnevegen 3, N-4820 Froland (NO).

(74) Agent: **OSLO PATENTKONTOR AS;** Postboks 7007 M,
N-0306 Oslo (NO).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **METHOD FOR CHECKING WHETHER A MOBILE STATION SUPPORTS A LOCATION SERVICE (LCS) IN A PACKET SWITCHED MODE**

(57) Abstract: The present invention is related to LoCation Services (LCS) in General Packet Radio Service (GPRS). Because the specification of LCS was missing in the first versions of the technical specifications of GPRS, but already introduced in the GSM specifications, there will be a number of MSs having LCS capabilities when attached to circuit switched serving nodes (MSCs) but not when attached to packet switched serving nodes (SGSNs). When a location request for one such MS attached to both an MSC and an SGSN is directed to the SGSN first, an error may occur. The present invention discloses a method solving this problem by informing the associated HLR if the MS supports location service in packet switched mode or not at the time the MS attaches the network. The information is stored in the HLR, and when the location service node in the network receives a location request for that MS, the location node invokes the HLR for the information. If the MS does not support location service in packet switched mode, the HLR informs the location service node to firstly request the MS attached MSC for the location of the MS.

WO 03/034770 A1

Method for checking whether a mobile station supports a location service (LCS) in a packet switched mode.

Field of the invention

The present invention is related to LoCation Services (LCS) in General Packet Radio Service (GPRS). Terminology and abbreviations within the technical field of GPRS, well known for persons skilled in the art, will be used in this application, and reference is made to the 3GPP TS 23.271 specification for a detailed description of LCS.

Background of the invention

Higher data speed in cellular phone systems allows offering of new types of services. One of the service types that is expected to have a breakthrough with the launch of GPRS is the Localization Services. These are services providing mobile telephone users with information about where objects or persons are localized. This information may be presented on the user terminal on e.g. a digital map, or simply through statement of position, address or place name.

Further, Location Services may be considered as a network provided enabling technology consisting of standardised service capabilities, which enable the provision of location applications. The main component in LCS is the GMLC (Gateway Mobile Location Centre), to which all location requests are transmitted, providing the requested location from the mobile network. The application(s) may be service provider specific, for example tracking of persons or vehicles. However, the description of the numerous and varied possible location applications that are enabled by this technology are outside the scope of the present document.

As mentioned above, LSC will probably not become common in the GSM environment before the launch of GPRS. However, LSC was specified for GSM already in GSM 03.71, Release 4, but not in originally for GPRS. LSC was introduced in GPRS as late as in the 3GPP TS 23.271 released in 2001.

As a result of this, a large number of GPRS/GSM MSs will support LSC for GSM, but not for GPRS. This applies for MSs that have already been manufactured and for those being manufactured in the near future. Consequently, there will exist a large number of MSs with inconsequent LCS capabilities in many years ahead.

The problem then occurs when an LCS Client (another MS, a service node etc.) wants to track the position of a Mobile Station (MS) via GPRS, i.e. via an SGSN node, and that MS does not support LCS Capability for GPRS.

Due to that LCS for GPRS is standardised in a later release of the standard than LCS for GSM and even later than GPRS itself, it is entirely possible (even likely) to have MSs that support both LCS for GSM and GPRS, but does not support LCS for GPRS.

In this case, if the request for positioning is initially sent to the SGSN node, the positioning may fail in SGSN if the MS does not support LCS for GPRS, whereas if the request had been sent to MSC node (circuit switched GSM), it would have been successful.

The only known solution today is that the SGSN returns an error message, and that the GMLC due to this retransmits the location request towards the MSC.

The problem with the solution as described above is that the fetching of the positioning might be time critical, meaning that the response will be returned to the LCS Client too late if we first have to try against SGSN and then perform a second try against MSC.

Summary of the invention

The main object of the present invention is to overcome the above-identified problems. This is achieved by a method defined in the enclosed claim 1.

Brief description of the drawings

Figure 1 is an overview of the nodes involved in a Location Request and the interaction between them,

Figure 2 shows an example of the message sequence of an attach procedure according to the 3GPP TS 23.060 specification,

Figure 3 shows an example of the message sequence of a mobile terminated location request according to the 3GPP TS 23.271 specification,

Detailed description

The present invention discloses a method to inform the Home Location Register (HLR) in a GPRS/GSM network about the LCS Capabilities of the attached MS. When Gateway Mobile Location Centre (GMLC) then invokes the HLR for routing information (i.e. SGSN and/or MSC address), the HLR will based on the information from SGSN be able to tell GMLC whether it should try SGSN or MSC first, and by that having

a larger likelihood to succeed with the positioning attempt of the subscriber.

The attached figures show the interactions between the different nodes involved in the Location Request.

According to the present invention, when an MS performs a GPRS Attach towards SGSN, it will inform the SGSN about the LCS capabilities it supports for GPRS network. When the MS roams into another SGSN, the LCS Capability information will also be informed to the new SGSN.

During the Attach or Inter SGSN Routing Area Update procedures the SGSN will update HLR about the MS's new location. According to the present invention, the SGSN shall then in addition include the LCS Capability information for this MS in the signalling procedure against HLR.

The HLR will now be informed about the LCS Capabilities for this subscriber, and can then use this information later on when a positioning is to be performed for this subscriber.

Consider that an LCS Client now wants to provide the position of this subscriber:

- 1) The LCS Client sends the Location Request towards the GMLC.
- 2) GMLC interrogates HLR for retrieval of routing information. The HLR will return routing information for SGSN or MSC or both, depending on where the subscriber is attached (GPRS Attached or IMSI Attached or both). As the HLR today only knows that

the subscriber has attached to an SGSN and/or MSC, there is no valid information to prioritise the possibilities for a successful positioning on either SGSN or MSC in the cases when the subscriber is attached to both domains. However, when the feature of the present invention is supported, the HLR will, based on the information concerning the MS's Capabilities for LCS, be able to inform the GMLC if it should try the SGSN or the MSC first. HLR should then, for the subscribers where SGSN have indicated that LCS for GPRS is not supported, still return both SGSN and MSC address, but indicate that the MSC is the preferred one.

- 3) GMLC will then send the Location Request to the MSC. MSC then starts the location procedure against the MS and preferably gets the position, which then is returned via GMLC back to the LCS Client.

The sequence in figure 2 shows an example of the Attach procedure, as described in the 3GPP TS 23.060 specification. In the following, the sequence adjusted according to the present invention will be described.

- 1) For GPRS, the MS initiates the attach procedure by the transmission of an Attach Request message to the SGSN. The message contains among others the MS's GPRS LCS capabilities. In this example the MS does not support any LCS Capabilities for GPRS.
- 2) If the SGSN number has changed since the GPRS detach, or if it is the very first attach, then the SGSN informs the HLR:

- a) The SGSN sends an Update Location to the HLR.
The information that the MS does not support LCS for GPRS is included.
 - b) The HLR acknowledges the Update Location message by sending an Update Location Ack to the SGSN.
- 3) The SGSN sends an Attach Accept message to the MS.

The sequence in figure 3 shows an example of a Mobile Terminated Location Request (MT-LR) procedure, as described in the 3GPP TS 23.271 specification. In the following, the procedure adjusted according to the present invention will be described.

- 1) An external LCS client requests the current location of a target UE from a GMLC.
- 2) GMLC sends a SEND_ROUTING_INFO_FOR_LCS message to the home HLR/HSS of the target UE to be located with the IMSI, PDP address or MSISDN of this UE as input parameters.
- 3) The HLR/HSS then returns one or several of the addresses, the current SGSN and/or MSC and whichever of the IMSI and MSISDN that was not provided in step (2) for the particular UE. Note that HLR may prioritise between the MSC or SGSN address sent to GMLC. This priority criterion is based on the present invention, and by that, HLR will in this example prioritise the MSC address.
- 4) In case GMLC receives only the MSC address, the MT LR proceeds as the CS-MT-LR procedure against MSC. In

case GMLC receives only the SGSN address, the MT LR proceeds as the PS-MT-LR procedure against SGSN. In case the GMLC receives several of the following addresses, SGSN and/or MSC, it has to decide where to send the location request. According to the present invention, the decision will be based on the prioritisation made by HLR, and in this example GMLC will therefore request the MSC first.

- 5) When the location of the subscriber is returned from MSC the GMLC sends the location service response to the LCS client.

The main advantage with the present invention is that since the HLR will be able to make a proper prioritisation between the different possible routing information addresses for a location request, and not just randomly as today, the GMLC will be able to select the one having a larger likelihood for a successful location request. For time critical location requests, this might be the difference between an acceptable and an unacceptable response seen from the LCS Client point of view.

The present invention is also applicable to circuit switched core networks in GSM systems, and core networks.

P a t e n t c l a i m s

1. Method for a location service provided by a location node in a cellular network wherein Mobile Stations (MSs) are being able to operate, simultaneously or not, in both a packet switched and a circuit switched mode, the MSs are attached to a first serving node in case of packet switched mode, and to a second serving node in case of circuit switched mode, the cellular network includes a register containing i.a. information concerning the location of the MSs,

c h a r a c t e r i z e d i n the following steps:

- a) when one of the MSs attaches the first serving node, informing the register whether the MS supports the location service in packet switched mode or not, or when one of the MSs attaches the second serving node, informing the register whether the MS supports the location service in circuit switched mode or not,
- b) when a location request for the MS is received at the location node, requesting the register for serving node address, and on response to that, checking, in the register, whether the MS supports the location service in packet switched mode or not, and if not, informing the location node that the location request shall be directed to the second serving node.

2. Method according to claim 1,

c h a r a c t e r i z e d i n that the cellular network is a GSM/GPRS network, the first serving node is an SGSN,

the second serving node is an MSC and the register is an HLR.

3. Method according to claim 2, characterized in that the location service is the location service defined in the 3GPP TS 23.271 specification, and the location node is a GMLC.
4. Method according to claim 1 or 2, characterized in that in step a), the information whether or not the MS supports the location service in packet switched mode is included in an Attached Request message transmitted from MS to the SGSN and in an Update Location message transmitted from the SGSN to the HLR.
5. Method according to one of the claims 1, 2, or 3, characterized in that in step b), the request to the register for the serving node address is a Send Routing Info for LCS message, and the information regarding that the location request shall be directed to the second serving node is included in a Send Routing Info for LCS acknowledge.

1/3




Fig. 1




Fig. 2

3/3




Fig. 3

INTERNATIONAL SEARCH REPORT

Intern: Application No

PCT/NU 02/00377

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04Q7/38

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal, WPI Data, PAJ, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 00 25545 A (NOKIA NETWORKS OY ;HAUMONT SERGE (FI); MUHONEN AHTI (FI); PUUSKARI) 4 May 2000 (2000-05-04) page 2, line 26 -page 3, line 16 page 4, line 31 -page 5, line 13 abstract; figure 2	1-5
A	WO 00 35236 A (ERICSSON INC) 15 June 2000 (2000-06-15) page 4, line 17 -page 5, line 2 abstract	1-5
A	WO 01 56321 A (NOKIA MOBILE PHONES LTD ;VAENTTINEN VEIJO (FI)) 2 August 2001 (2001-08-02) abstract	1-5

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

5 February 2003

Date of mailing of the international search report

24.02.2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

CATHARINA KARLSSON/JA

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/NO 02/00377

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0025545	A	04-05-2000	FI 982331 A	28-04-2000
			AU 1049500 A	15-05-2000
			CN 1324553 T	28-11-2001
			EP 1125459 A1	22-08-2001
			WO 0025545 A1	04-05-2000
			JP 2002529031 T	03-09-2002

WO 0035236	A	15-06-2000	US 6219557 B1	17-04-2001
			AU 2357400 A	26-06-2000
			BR 9916129 A	04-09-2001
			CN 1335035 T	06-02-2002
			EP 1135956 A1	26-09-2001
			JP 2002532990 T	02-10-2002
			WO 0035236 A1	15-06-2000

WO 0156321	A	02-08-2001	FI 20000149 A	27-07-2001
			AU 3028601 A	07-08-2001
			WO 0156321 A1	02-08-2001
			GB 2373688 A	25-09-2002
			US 2001009857 A1	26-07-2001
